01-2016

County

CHICKASAW COUNTY APPLICATION FOR ANNUAL OVERSIZE/OVERWEIGHT PERMIT

(Valid For One Power Unit Only)

		•			• • • • • • • • • • • • • • • • • • • •				
Send Application To:			•	plication					
Chickasaw County Engineer's Office			Annual Oversize Permit Fee: \$50.00						
P.O. Box 316 New Hampton, Iowa 50659			Annual Oversize/Overweight Permit Fee: \$400.00						
-	(641) 394-232		Payment: Cash/Check# Make checks payable to: Chickasaw County						
	41) 394-5280	•	IVIO	011001	a payabic	to. Official	saw County		
Issued To:					FAX No:				
Address:								_	
P) 11 14) 7						· · · · · · · · · · · · · · · · · · ·			
Power Unit Year & Make		Power Unit License No. &		State	Power	Unit Registered Weight			
Axle Weights	Sin	gle	Tar	ndem	Trip	ple	Quad	_	
Please	indicate the m	naximum on l	lenath. v	vidth he	ight and w	eight vou	ı will need	_	
Object of Load:		-	iongin, r	*10:11, 110	ight and v	reignit you	t will fiecu,	_	
Overall Length	Width	Height	Total We		ight		Projections		
					-	Front	Rear		
Date Requesting Perm	it to Start		Pei	rmit Expi	ration Date			_	
Requested By		Phone Number				-			
Maximum dimensions	and weight allo	wed on a \$50	.00 annı	ial overs	ize permit	are:		-	
weight - 80	,000 pounds								
	x 12' 5" wide x								
							unless the route		
*120' long :	x 16' wide x 15'	t least 4-lane 5" high - trip	routes or	trip route	s are optai	nea trom i	Motor Carrier Services.		
	12' 5" wide x 14					ng hay.			
Maximum dimensions							mit are	_	
	6,000 pounds	ποα οπ α φπο	0.00 4111	idai OVO	3120/04014	veignt per	niit are.		
*120' long :	x 13' 5" wide x	15' 5" high - tr	ip routes	must be	obtained.				
Carrier will be respons	ble for obtainin	a necessarv r	oute app	roval pri	or to move	Current c	tetour embargo and	-	
vertical clearance infor	mation is neces	ssary for routi	ng. It is	the resp	onsibility o	f the carrie	er to route themselves		
around low clearances	, construction p	rojects, emba	argoed ro	ads and	bridges. If	carrier de	monstrates		
inability to self-issue, th									
Permits can be issued	only for transpo	orting, single a	articles th	nat excee	d statutory	size unles	ss the inclusion of		
additional articles does	not cause the	size or weight	t to furthe	er exceed	the statute	ory limits.	less assumed at the Africa		
Certificate of Pulic Liab vehicle for which the pe			s ur \$ iul	J,UUU/ ֆ ∠l	υσφιυυυ,υι	ovo must	be carried in the		
			ad for th	o mar	ant of the				
The above permit with load on those seconda	ry roads within	the following	counties:	e moven	ient of the a	above des	cribed vehicle and		

Disclosure Statement: The information furnished on this application will be used by Chickasaw County to prepare and issue permits.

All information applicable to a given permit is required and is public information. Failure to complete the application as required will

Date Approved

Receipt No.

Permit No.

Authorized Signature



IOWA GENERAL PROVISIONS FOR OVERSIZE LOAD PERMIT

The State of lowa, the lowa Department of Transportation, and any other permit issuing authority assume no responsibility for the property of the permit holder. During movement under permit, the permit holder must meet the terms and conditions of the permit and must take all reasonable precautions to protect and safeguard the lives and property of the traveling public and adjacent property owners. A copy of a current certificate of public liability insurance in the amounts of \$100,000 bodily injury each person, \$200,000 bodily injury each occurrence, and \$50,000 property damage must be carried in the vehicle for which the permit has been Issued. Nothing shall exempt the permit holder from compliance with any load limitations that have been or might be established on any bridge or road posted with embargo signs. The permit and any revisions will be void if the actual weights or dimensions exceed what is indicated on the permit or its revisions. Permits can be issued only for loads that are a single article that cannot be reasonably broken down to make it legal in size and weight. The permit must be carried in the cab of the vehicle for which it has been issued and be available for inspection. Proof of liability insurance may be either in writing or in electronic format.

Movement is allowed seven days a week except for designated holidays and for special events when abnormally high traffic counts can be expected. The designated holidays are Memorial Day, Independence Day, and Labor Day. No movement will be allowed on these holidays or after 12 noon on days preceding these holidays and hollday weekends that include holidays falling on Monday, except as provided for in lowa Code 321.457,

Annual permits: Routes must be checked for construction restrictions and clearance problems using the vertical clearance maps, bridge embargo maps, pavement restriction maps, and the 511la.org website prior to moving under permit. Maps can be found at lowadot.gov/mvd/motorcarriers.

Escort requirements: Escorts must be at least 18 years old, possess a valid Class A, B, C, or D driver's license, and carry proof of public liability insurance In the amounts of \$100,000/\$200,000/\$50,000. The escort vehicle must be approximately the size of a normal passenger automobile or pickup and must have a flashing or strobe amber light that shall be burning while escorting a permit load. The escorting vehicle shall not be used to tow a trailer while performing escorting duttes. The escort shall not assume responsibility for stopping traffic. An on-duty peace officer, as defined in lowa Code section 321.1, shall be contacted to provide any traffic control needed.

Required warning devices and escort requirements for vehicles operating under permit

	Flags/Signs	Lights	Escorts .		
			Four-lane	Two-lane	
Léngth					
75'1" up to and including 85'	Yes	Not required	Not required	Not required	
Over 85' up to and including 120'	Yes	Yes	Not required	Not required	
Over 120'	Yes	Not required	Rear	Rear	
Projections					
Front: over 25'	Not required	Yes	Not required	Not required	
Rear; over 4' up to and including 10'	Flags only	Not required	Not required	Not required	
Rear: over 10'	Flags only	Yes	Not required	Not required	
Height					
Over 14'6" up to 20'	Yes	Not required	Front with a height pole	Front with a height pole	
Welght .				E.,	
Over 80,000 lbs.	Not required	Yes	Nat required	Not required	
Width				· ·	
Over 8'6" up to 12'	Yes	Not required	Not required	Not required	
Over 12' up to and Including 14'6"	Yes	Not required	Rear*	Front*	
Over 14'6" up to and including 16'6"	Yes	Not required	Rear*	Front	
Over 16'6" up to and including 18'	Yes	Not required	Rear	Front	

in fleu of an escort, a vehicle can display an amber light or strobe on the power unit and on the rear extremity of the load.

Lighting requirements: A flashing or strobe amber light that is visible for at least 500 feet and provides 360-degree warning, mounted on the towing unit is required. An escort can be used in fleu of amber light.

Signs and flags: A sign reading "Oversize Load" must be at least 18 inches high by 7 feet long with a minimum of 10-inch black letters with a 1 1/2-inch stroke, on a yellow background, and mounted on the front bumper and on the rear of the load. A rear sign for mobile homes must be mounted at least 7 feet above the highway surface, measuring from the bottom of the sign. Flags must be red or orange fluorescent and at least 18 inches square. Flags must be mounted as follows: one flag at each front corner of the lowing unit and one flag at each rear corner of the load. In addition, there must be a flag at any additional protrusion in the width of the load. The signs or warning devices must be mounted so they can be removed or covered when the vehicle is within legal dimensions.

Permitted tandem axle weights: Vehicles operating under a permit issued pursuant to lowe Code 321E.8, 321E.9, or 321E.9A may have a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor and a gross weight not to exceed 46,000 pounds on a single-landern axie of the truck tractor ax or semitraller if each axle of each tandem group has at least four tires. No single axle of the tandem group may exceed 24,000 pounds. If the tandem axle is within a larger group of exles, the maximum weight of that specific group of exles shall not exceed 20,000 pounds per exle.

Requirements for continuous moves: Vehicles and loads may travel by permit between 1/2 hour after sunset and 1/2 hour before sundse if, in addition to the general provisions and general requirements specified by the permit, the following conditions are met.

- a. Dimensions shall not exceed:

 - (1) Width: 11 feet.(2) Height: 14 feet, 6 inches.
 - (3) Length: 100 feet.
 - (4) Weight: Permitted axle limits.
- b. Travel must be on roadways with a minimum width of 22 feet and minimum lane width of 11 feet.
- Safety lighting shall be provided at the widest part of a load. The lamps may be placed at the outer ends of the load itself or on appurtenances that are equal in width to the widest part of the load and positioned at both extreme front and rear of the vehicle or trailer as follows.
 - (1) One lighted red lamp on each side at the rear of the load.
 - (2) One lighted yellow or amber lamp on each side at the front of the load.